

Low-voltage Battery System



T-BAT-SYS-LV D53



High Performance

- Peak discharge current: 200A for 10s
- Cycle life > 6000 times



Assured Reliability

- LiFePO4 battery cell & high-performance processors
- IP65 protection degree



Smart Management

- Remote fault diagnosis, upgrade and maintenance
- AI-driven intelligent algorithms for high SOC and accuracy



Flexible Adaptability

- Floor or wall mounting optional
- Modular design, expandable to 16 units in parallel

T-BAT-SYS-LV D53

SYSTEM PARAMETERS								
TYPE / MODEL	T-BAT LD53	T-BAT LD106	T-BAT LD159	T-BAT LD212	T-BAT LD265	T-BAT LD318	T-BAT LD371	T-BAT LD424
Number of Modules	1	2	3	4	5	6	7	8
Nominal capacity	5.3 kWh	10.6 kWh	15.9 kWh	21.2 kWh	26.6 kWh	31.9 kWh	37.2 kWh	42.5 kWh
Usable capacity (90% DOD) ^①	4.7 kWh	9.5 kWh	14.3 kWh	19.1 kWh	23.9 kWh	28.7 kWh	33.5 kWh	38.3 kWh
Max. output current ^②	100 A	120 A						
Peak discharge current	200 A, 10s							

SYSTEM PARAMETERS								
TYPE / MODEL	T-BAT LD477	T-BAT LD530	T-BAT LD583	T-BAT LD636	T-BAT LD689	T-BAT LD742	T-BAT LD795	T-BAT LD848
Number of Modules	9	10	11	12	13	14	15	16
Nominal capacity	47.9 kWh	53.2 kWh	58.5 kWh	63.8 kWh	69.2 kWh	74.5 kWh	79.8 kWh	85.1 kWh
Usable capacity (90% DOD) ^①	43.1 kWh	47.9 kWh	52.7 kWh	57.5 kWh	62.3 kWh	67.0 kWh	71.8 kWh	76.6 kWh
Max. output current ^②	120 A							
Peak discharge current	200 A, 10s							

GENERAL INFORMATION	
Weight	48.5 kg
Dimension (L x W x H)	645 x 150 x 430 mm
Nominal voltage	51.2 V
Operating voltage range	45 ~ 58 V
Battery type	Lithium iron phosphate
Communication port	CAN / RS485
Operation temperature	0 ~ 53°C (charge) - 20 ~ 53°C (discharge)
Storage temperature	30 ~ 50°C (6 months) - 20 ~ 30°C (12 months)
Ingress protection	IP65
Colling concept	Natural cooling
Relative humidity	5 ~ 95% RH (Non-condensing)
Altitude	< 3000 m
Warranty ^④	10 years
Cycle life ^③ [90% DOD]	> 6000
Certification	IEC62619, IEC62040, CE, UN38.3

① Test conditions: 90% DOD, 0.2C charge & discharge @+25°C

② Current is affected by the number of batteries connected in parallel as well as temperature and SOC

③ 25°C ± 2°C, 0.5C / 0.5C, 70% EOL > 6000

④ The warranty is due whichever reached first of warranty period or energy throughput