



C&I On-grid Inverter



X3-MEGA G2

40kW/50kW/60kW



High Efficiency

- Up to 98.4% efficiency
- Max. 32A MPPT current
- 180~1000Vdc MPPT voltage range
- 150% PV oversizing, 110% overloading output



Assured Safety

- IP66 protection
- SPD Type II
- Smart string current monitoring
- 24 hours operation monitoring



Intelligent Design

- Night-time reactive power compensation
- Smart air cooling enhances fan longevity
- Heat dissipation reduces system weight & size by over 10%
- Smart I-V Curve diagnosis



Flexible Adaptability

- Built-in export power control
- Remote setting and upgrading
- Aluminium AC cable connection available
- Max. 6 MPPTs, 2 strings per MPP tracker

	X3-MGA-40K-G2	X3-MGA-50K-G2	X3-MGA-60K-G2		
PV INPUT					
Max. recommended PV array power	60 kWp	75 kWp	90 kWp		
Max. PV input voltage ^①		1100 V			
Nominal PV input voltage		600 V			
Operating voltage range		200 ~ 1000 V			
MPPT voltage range ^②		180 ~ 1000 V			
Start-up voltage		200 V			
No. of MPP trackers / Strings per MPP tracker	4 / 2	5 / 2	6 / 2		
Max. input current per MPPT		32 A			
Max. input short circuit current per MPPT		46 A			
AC OUTPUT					
Rated output power	40 kW	50 kW	60 kW		
Rated output current ^③	60.6 A / 58 A	75.8 A / 72.5 A	90.9 A / 87 A		
Max. output apparent power	44 kVA	55 kVA	66 kVA		
Max. output continuous current ^③	66.7 A / 63.8 A	83.3 A / 79.7 A	100 A / 95.7 A		
Nominal AC voltage		3 / (N) / PE, 220 / 380 V 3 / (N) / PE, 230 / 400 V			
Nominal AC frequency		50 Hz / 60 Hz			
AC frequency range ^④		50 ± 5 Hz / 60 ± 5 Hz			
Adjustable Power Factor range		~ 1 (0.8 lagging to 0.8 leading)			
THDi (rated power)		< 3%			
EFFICIENCY					
Max. efficiency		98.4%			
European efficiency		98.1%			
ENVIRONMENT LIMIT					
Ingress protection		IP66			
Operating ambient temperature range ^⑤		-25 ~ 60°C			
Max. operating altitude ^⑥		4000 m			
Relative humidity		0 ~ 100% RH			
Overvoltage Category		Mains: III, PV: II			
GENERAL					
Dimensions (W × H × D)		630 × 521 × 286 mm			
Net weight	44.0 kg	44.5 kg	45.5 kg		
Cooling concept		Smart cooling			
Communication interfaces		RS485, DRM			
Power consumption (night)		< 2 W			
Topology		Non-isolated			
Certificates and approvals	IEC/EN 62109-1, IEC/EN 62109-2, NB/T 32004, EN 50549, AS4777.2, VDE4105, IEC 61727, IEC 62116, IEC 61683, IEC 60068, EN 50530, NB/T 32004				
PROTECTION					
Protections	Over / under voltage protection, DC isolation protection, DC reverse-polarity protection, Grid monitoring, DC injection monitoring, Back feed current monitoring, Residual current detection, AC overcurrent protection, String fault detection, AC overcurrent protection, AC short-circuit protection				
Active anti-islanding method	Frequency shift				
Surge protection (DC / AC)	DC: Type II, AC: Type II				
Arc-fault circuit interrupter (AFCI)	Optional				
AC auxiliary power supply (APS)	Optional				
Anti-PID	External				

^①The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage the inverter.

^②Input voltage exceeding the MPPT voltage range may trigger inverter protection.

^③The two data refer to different grid voltage 220V/230V (75~125kW models) or 500V/540V (136~150kW models).

^④The AC frequency range may vary from different country codes.

^⑤Derating above +45°C.

^⑥Derating above 3000 m.